

View Online at <https://aerobasegroup.com/nsn/5925-01-464-1195>

Body Style:

Multipole-single actuator type

Body Length:

5.800 inches

Body Width:

1.026 inches

Body Height:

2.609 inches

Case Material:

Plastic

Pole Quantity:

3

Features Provided:

High inrush protection

Maximum Continuous Load Current Rating Per Pole:

100.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

7500.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

3600.000 at 100 pct all locations

Special Features:

Unsealed; front mounted with 6-32 threaded inserts

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0