

View Online at <https://aerobasegroup.com/nsn/5925-01-464-1195>

**Body Style:**

Multipole-single actuator type

**Body Length:**

5.800 inches

**Body Width:**

1.026 inches

**Body Height:**

2.609 inches

**Case Material:**

Plastic

**Pole Quantity:**

3

**Features Provided:**

High inrush protection

**Maximum Continuous Load Current Rating Per Pole:**

100.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

7500.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

150.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Internal Trip Release Configuration:**

Series trip all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

3600.000 at 100 pct all locations

**Special Features:**

Unsealed; front mounted with 6-32 threaded inserts

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Terminal Type And Quantity:**

6 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0