

View Online at <https://aerobasegroup.com/nsn/5925-01-466-5073>

**Body Style:**

Multipole-single actuator type

**Body Length:**

5.125 inches

**Body Width:**

3.108 inches

**Body Height:**

3.520 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

2.750 inches

**Center To Center Distance Between Terminals Parallel To Width:**

1.026 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

4.089 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.360 inches

**Boss Height:**

0.220 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

6 threaded stud

**Maximum Continuous Load Current Rating Per Pole:**

100.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

150.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

150.0 all locations

**Reset Method:**

Electric

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

3 toggle

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.138 inches

**Trip Release Duty Cycle:**

Continuous all locations

**Reset Actuator Voltage Rating And Type In Volts:**

240.0 ac

**Special Features:**

Turrets-double stop type

**Frequency In Hertz:**

400.0 all locations

**Unpackaged Unit Weight:**

2.000 pounds

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0