

View Online at <https://aerobasegroup.com/nsn/5925-01-468-6257>

Body Style:

Multipole-single actuator type

Body Length:

Between 5.115 inches and 5.135 inches

Body Width:

Between 3.098 inches and 3.118 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 3.480 inches and 3.614 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.994 inches and 1.056 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.740 inches and 2.760 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.042 inches and 2.062 inches

End Application:

5865-01-437-4914

Boss Height:

Between 0.210 inches and 0.230 inches

Mounting Surface To Terminal End Distance:

Between 3.460 inches and 3.580 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 threaded hole

Maximum Continuous Load Current Rating Per Pole:

60.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

60.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Relay trip all locations

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

13.000 at 125 pct all locations and 90.000 at 150 pct all locations

Trip Release Ambient Temperature Rating:

40.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0