

View Online at <https://aerobasegroup.com/nsn/5925-01-469-6667>

Body Style:

Multipole-single actuator type

Body Length:

2.000 inches

Body Width:

1.325 inches

Body Height:

1.770 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Width:

0.825 inches

End Application:

Weapons system-radar set, an/pps-5 (v) 1

Boss Height:

0.250 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

2 clip

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations and 250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

50.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

800.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Nontrip free

Manual Actuator Type And Quantity:

1 toggle

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

0.900 at 125 pct first location and 10.000 at 125 pct first location

Switch Voltage Rating And Type In Volts:

250.0 ac and 28.0 dc

Special Features:

White translucent neon illuminated rocker handle; operating temperature minus 40 degrees c to 85 degrees c

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Terminal Type And Quantity:

4 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0