NSN 5925-01-473-0632

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-473-0632

#### **Body Style:**

Rectangular dimensional envelope

**Overall Length:** 

1.470 inches

# **Overall Height:**

0.390 inches

**Overall Width:** 

0.820 inches

#### Mounting Slot Width:

0.210 inches

#### **Case Material:**

Plastic

#### **End Application:**

2320-01-465-2174

#### **Pole Quantity:**

2

#### Mounting Facility Type And Quantity:

2 slot

#### Maximum Continuous Load Current Rating Per Pole:

10.0 amperes dc single location

#### **Operating Voltage Type And Rating Per Pole In Volts:**

36.0 dc single location

### Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10.0 dc single location

#### **Circuit Protection Type:**

Overcurrent single location

#### Trip Release Method:

Thermal single location

#### Trip Release Characteristic:

Instantaneous all locations

# Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

100.0 single location

# **Reset Method:**

Manual

# Main Contact Tripping Mechanism Type:

Trip free

# Internal Trip Release Configuration:

Relay trip single location

# Trip Release Ambient Tempurature Rating:

40.0 degrees celsius single location

# Product Name:

Circuit breaker, 10amp

# NSN 5925-01-473-0632

Circuit Breaker - Page 2 of 2



# Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A030a0