## NSN 5925-01-473-0635

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-473-0635

**Body Style:** Single pole type **Body Diameter:** 0.820 inches **Mounting Slot Width:** 0.210 inches **Bushing Length:** 0.120 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Diameter:** 0.100 inches **End Application:** 2320-01-465-2174 **Mounting Surface To Terminal End Distance:** 1.350 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 slot **Maximum Continuous Load Current Rating Per Pole:** 20.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 36.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 20.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location **Trip Release Characteristic:** Instantaneous single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 20.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** 

Trip free

**Internal Trip Release Configuration:** 

Relay trip single location

**Trip Release Ambient Tempurature Rating:** 

40.0 degrees celsius single location

## NSN 5925-01-473-0635

Circuit Breaker - Page 2 of 2



| Product Name:               |
|-----------------------------|
| Circuit breaker, 20 amp     |
| Special Features:           |
| Push to reset button        |
| Terminal Type And Quantity: |
| 1 bus bar                   |
| Shelf Life:                 |
| N/a                         |
| Unit Of Measure:            |
|                             |
| Demilitarization:           |
| No                          |

**Fiig:** A030a0