

View Online at <https://aerobasegroup.com/nsn/5925-01-473-0646>

Body Style:

Rectangular dimensional envelope

Overall Length:

1.350 inches

Overall Height:

0.390 inches

Overall Width:

0.820 inches

Mounting Slot Width:

0.210 inches

Case Material:

Plastic

End Application:

2320-01-465-2174

Pole Quantity:

2

Mounting Facility Type And Quantity:

2 slot

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

36.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

20.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Instantaneous single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

100.0 all locations

Ultimate Trip Time Per Pole In Seconds:

15.000 all locations

Reset Method:

Automatic

Internal Trip Release Configuration:

Relay trip single location

Trip Release Ambient Temperature Rating:

40.0 degrees celsius single location

Product Name:

Circuit breaker, 20 amp

Special Features:

Used on mk23, mk25, mk27, mk28, mk29, mk30

Terminal Type And Quantity:

2 bus bar

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0