

View Online at <https://aerobasegroup.com/nsn/5925-01-473-0646>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

1.350 inches

**Overall Height:**

0.390 inches

**Overall Width:**

0.820 inches

**Mounting Slot Width:**

0.210 inches

**Case Material:**

Plastic

**End Application:**

2320-01-465-2174

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

2 slot

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

36.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

20.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Instantaneous single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

100.0 all locations

**Ultimate Trip Time Per Pole In Seconds:**

15.000 all locations

**Reset Method:**

Automatic

**Internal Trip Release Configuration:**

Relay trip single location

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius single location

**Product Name:**

Circuit breaker, 20 amp

**Special Features:**

Used on mk23, mk25, mk27, mk28, mk29, mk30

**Terminal Type And Quantity:**

2 bus bar

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0