

View Online at <https://aerobasegroup.com/nsn/5925-01-474-6045>

**Body Style:**

Multipole-multiple actuator type

**Bushing Length:**

Between 0.332 inches and 0.380 inches

**Body Length:**

1.562 inches

**Body Width:**

1.937 inches

**Case Material:**

Ceramic or mica or plastic

**Center To Center Distance Between Terminals Parallel To Length:**

0.906 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 0.594 inches and 0.656 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 1.359 inches and 1.389 inches

**End Application:**

1430-01-418-4396

**Mounting Surface To Terminal End Distance:**

1.950 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

1 threaded bushing w/panel seal

**Features Provided:**

High inrush protection

**Maximum Continuous Load Current Rating Per Pole:**

3.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations and 50.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

300.0 ac all locations and 500.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

800.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Nontrip free

**Internal Trip Release Configuration:**

Relay trip all locations

**Thread Size:**

0.375 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.240 at 400 pct all locations

**Inclosure Protection Type For Which Designed:**

Tamperproof and salt water resistant and fungus proof

**Switch Terminal Type:**

Tab w/screw

**Frequency In Hertz:**

60.0 all locations or 400.0 all locations

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

6 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0