

View Online at <https://aerobasegroup.com/nsn/5925-01-475-0485>

**Bushing Length:**

0.380 inches

**Body Length:**

1.500 inches

**Body Width:**

0.625 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

0.875 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.625 inches

**Mounting Surface To Terminal End Distance:**

1.780 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

1 threaded bushing and 2 threaded hole

**Maximum Continuous Load Current Rating Per Pole:**

15.0 amperes ac all locations and 7.5 amperes ac all locations and 20.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

120.0 ac all locations and 240.0 ac all locations and 50.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

800.0 ac all locations and 800.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Automatic

**Main Contact Tripping Mechanism Type:**

Trip free

**Internal Trip Release Configuration:**

Series trip w/auxiliary load terminal all locations

**Thread Size:**

0.375 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

8.000 at 125 pct all locations

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

6 wire hook

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A030a0