NSN 5925-01-477-4716

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-477-4716

| Bushing Length: |
|-------------------------------------------------------------------------|
| Between 0.219 inches and 0.281 inches |
| Body Length: |
| 1.840 inches |
| Body Width: |
| 0.770 inches |
| Body Height: |
| Between 1.319 inches and 1.381 inches |
| Case Material: |
| Plastic |
| Pole Quantity: |
| 3 |
| Mounting Facility Type And Quantity: |
| 1 threaded bushing |
| Thready Qty Per Inch (tpi): |
| 32 |
| Maximum Continuous Load Current Rating Per Pole: |
| 15.0 amperes ac all locations |
| Operating Voltage Type And Rating Per Pole In Volts: |
| 120.0 ac all locations |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: |
| 2000.0 ac all locations |
| Circuit Protection Type: |
| Overcurrent all locations |
| Trip Release Method: |
| Thermal all locations |
| Trip Release Characteristic: |
| Time delay all locations |
| Internal Trip Release Configuration: |
| Series trip all locations |
| Thread Size: |
| 0.438 inches |
| Trip Release Ambient Tempurature Rating: |
| 25.0 degrees celsius all locations |
| Frequency In Hertz: |
| 400.0 all locations |
| Thread Series Designator: |
| Uns |
| Terminal Type And Quantity: |
| 6 screw |
| Shelf Life: |
| NI/a |

N/a

NSN 5925-01-477-4716

Circuit Breaker - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A030a0