

View Online at <https://aerobasegroup.com/nsn/5925-01-479-7742>

Body Style:

Multipole-single actuator type

Bushing Length:

0.380 inches

Body Length:

1.500 inches

Body Width:

1.875 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.875 inches

Center To Center Distance Between Terminals Parallel To Width:

0.625 inches

Fragility Factor:

Moderately rugged

End Application:

5820-01-454-0338

Mounting Surface To Terminal End Distance:

1.780 inches

Pole Quantity:

3

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal and 2 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32 and 32

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.375 inches and 0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.200 at 200 pct all locations and 6.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Hermetically sealed

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Thread Series Designator:

Unef and unc

Terminal Type And Quantity:

6 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0