## NSN 5925-01-479-7765

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-479-7765 **Body Style:** Multipole-single actuator type **Body Length:** 3.000 inches **Body Width:** 2.234 inches **Body Height:** 2.922 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** 0.750 inches **End Application:** 5820-01-454-0338 **Boss Height:** 0.156 inches **Pole Quantity: Mounting Facility Type And Quantity:** 3 terminal **Maximum Continuous Load Current Rating Per Pole:** 35.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle

**Actuator Function:** 

Trip-reset

## NSN 5925-01-479-7765

Circuit Breaker - Page 2 of 2

No Fiig: A030a0



## Actuator Position Designation: At pole two Trip Delay Time In Seconds Per Rated Continuous Current: 15.000 at 200 pct all locations and 60.000 at 200 pct all locations Trip Release Ambient Tempurature Rating: 40.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations Terminal Type And Quantity: 6 screw Shelf Life: N/a Unit Of Measure: --Demilitarization: