NSN 5925-01-481-2099



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-481-2099 **Body Style:** Multipole-single actuator type **Body Length:** 6.000 inches **Body Width:** 4.500 inches **Body Height:** 3.160 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 5.130 inches **Center To Center Distance Between Terminals Parallel To Width:** 1.500 inches **Unthreaded Mounting Hole Diameter:** 0.190 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 5.130 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches **End Application:** Deck machine **Boss Height:** 0.125 inches **Pole Quantity:** 3 **Mounting Facility Type And Quantity:** 4 unthreaded hole **Maximum Continuous Load Current Rating Per Pole:** 100.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 480.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 22000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic-hydraulic all locations **Trip Release Characteristic:**

Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations

NSN 5925-01-481-2099 Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Trip Delay Time In Seconds Per Rated Continuous Current:
40.000 at 200 pct all locations and 125.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Fungus resistant
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Special Features:
Accessory 1212 monitors circuit breaker contact status and provides a remote signal indicating the circuit breaker contacts are open or
closed
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A030a0