

View Online at <https://aerobasegroup.com/nsn/5925-01-481-3442>

Body Length:

2.000 inches

Body Width:

2.250 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.765 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.660 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

End Application:

Uplink filter; weapon system-command control and communication sys 427m

Boss Height:

0.245 inches

Mounting Surface To Terminal End Distance:

2.040 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 threaded hole

Thread Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2500.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

200.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

3 toggle

Actuator Function:

Reset

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

2.200 at 200 pct all locations and 20.000 at 200 pct all locations

Special Features:

Mounted with no. 6-32 screws

Frequency In Hertz:

50.0 single location or 60.0 single location

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0