

View Online at <https://aerobasegroup.com/nsn/5925-01-481-8904>

Body Style:

Multipole-single actuator type

Bushing Length:

15.9 millimeters

Body Length:

50.8 millimeters

Body Width:

57.5 millimeters

Center To Center Distance Between Terminals Parallel To Length:

38.9 millimeters

Center To Center Distance Between Terminals Parallel To Width:

19.0 millimeters

Mounting Surface To Terminal End Distance:

56.7 millimeters

Pole Quantity:

3

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Characteristic:

Time delay all locations

Reset Method:

Manual

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Thread Size:

0.500 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 125 pct all locations and 120.000 at 125 pct all locations

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0