

View Online at <https://aerobasegroup.com/nsn/5925-01-482-9020>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

5.125 inches

**Body Width:**

2.114 inches

**Body Height:**

2.610 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

3.550 inches

**Center To Center Distance Between Terminals Parallel To Width:**

1.026 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.026 inches

**End Application:**

Hook cable support, retractable

**Pole Quantity:**

2

**Maximum Continuous Load Current Rating Per Pole:**

100.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

5000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

150.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Internal Trip Release Configuration:**

Series trip all locations

**Special Features:**

Coil rating - current coil amperes (30.000)

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0