

View Online at <https://aerobasegroup.com/nsn/5925-01-482-9962>

**Thread Pitch Diameters:**

+0.1141/+0.1169 inches

**Body Style:**

Single pole type

**Body Length:**

2.156 inches

**Body Width:**

0.745 inches

**Body Height:**

2.000 inches

**Case Material:**

Plastic

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.660 inches

**Boss Height:**

0.370 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 threaded hole

**Maximum Continuous Load Current Rating Per Pole:**

5.000 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

65.000 dc all locations and 277.000 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

3500.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.000 all locations

**Ultimate Trip Time Per Pole In Seconds:**

16.000 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Position Designation:**

At pole one

**Internal Trip Release Configuration:**

Series trip all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

16.000 at 125 pct all locations

**Trip Release Ambient Temperature Rating:**

40.000m degrees celsius all locations and 85.000 degrees celsius all locations

**Special Features:**

Actuator color - red dual (white)

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Thread Series Designator:**

M

**Terminal Type And Quantity:**

2 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0