

View Online at <https://aerobasegroup.com/nsn/5925-01-482-9962>

Thread Pitch Diameters:

+0.1141/+0.1169 inches

Body Style:

Single pole type

Body Length:

2.156 inches

Body Width:

0.745 inches

Body Height:

2.000 inches

Case Material:

Plastic

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.660 inches

Boss Height:

0.370 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded hole

Maximum Continuous Load Current Rating Per Pole:

5.000 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

65.000 dc all locations and 277.000 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

3500.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.000 all locations

Ultimate Trip Time Per Pole In Seconds:

16.000 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

16.000 at 125 pct all locations

Trip Release Ambient Temperature Rating:

40.000m degrees celsius all locations and 85.000 degrees celsius all locations

Special Features:

Actuator color - red dual (white)

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Thread Series Designator:

M

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0