

View Online at <https://aerobasegroup.com/nsn/5925-01-483-0111>

**Body Length:**

2.000 inches

**Body Width:**

0.750 inches

**Center To Center Distance Between Terminals Parallel To Length:**

1.530 inches

**Switch Contact Arrangement:**

Single pole, double throw

**Pole Quantity:**

1

**Maximum Continuous Load Current Rating Per Pole:**

15.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

2000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Auxiliary Trip Coil Voltage Type And Rating In Volts:**

125.0 ac all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Ultimate Trip Time Per Pole In Seconds:**

0.700 all locations and 12.000 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Auxiliary Switch Function And Quantity:**

1 control

**Internal Trip Release Configuration:**

Series/relay trip all locations

**Trip Release Duty Cycle:**

Continuous all locations

**Switch Location And Position Designation:**

Internal at pole one

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.700 at 125 pct all locations and 12.000 at 125 pct all locations and 0.350 at 150 pct all locations and 7.000 at 150 pct all locations and 0.130 at 200 pct all locations and 3.000 at 200 pct all locations and 0.030 at 400 pct all locations and 1.000 at 400 pct all locations and 0.015 at 600 pct all locations and 0.300 at 600 pct all locations and 0.010 at 800 pct all locations and 0.150 at 800 pct all locations and 0.008 at 1000 pct all locations and 0.100 at 1000 pct all locations

**Inclosure Protection Type For Which Designed:**

Corrosion resistant and moisture resistant and salt water resistant and shock resistant and vibration resistant

**Switch Terminal Type:**

Quick disconnect, male

**Switch Current Rating And Type In Amps:**

1.0 ac

**Switch Voltage Rating And Type In Volts:**

125.0 ac

**Special Features:**

Vde approved; toggle handle color is red - marked with white letters of on/off and i/o; approximate weight per pole 2.2 ounces; dielectric strength with auxiliary switched terminals 600 volts ac, 60 hertz

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Terminal Type And Quantity:**

2 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0