

View Online at <https://aerobasegroup.com/nsn/5925-01-483-0111>

Body Length:

2.000 inches

Body Width:

0.750 inches

Center To Center Distance Between Terminals Parallel To Length:

1.530 inches

Switch Contact Arrangement:

Single pole, double throw

Pole Quantity:

1

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Auxiliary Trip Coil Voltage Type And Rating In Volts:

125.0 ac all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Ultimate Trip Time Per Pole In Seconds:

0.700 all locations and 12.000 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Auxiliary Switch Function And Quantity:

1 control

Internal Trip Release Configuration:

Series/relay trip all locations

Trip Release Duty Cycle:

Continuous all locations

Switch Location And Position Designation:

Internal at pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

0.700 at 125 pct all locations and 12.000 at 125 pct all locations and 0.350 at 150 pct all locations and 7.000 at 150 pct all locations and 0.130 at 200 pct all locations and 3.000 at 200 pct all locations and 0.030 at 400 pct all locations and 1.000 at 400 pct all locations and 0.015 at 600 pct all locations and 0.300 at 600 pct all locations and 0.010 at 800 pct all locations and 0.150 at 800 pct all locations and 0.008 at 1000 pct all locations and 0.100 at 1000 pct all locations

Inclosure Protection Type For Which Designed:

Corrosion resistant and moisture resistant and salt water resistant and shock resistant and vibration resistant

Switch Terminal Type:

Quick disconnect, male

Switch Current Rating And Type In Amps:

1.0 ac

Switch Voltage Rating And Type In Volts:

125.0 ac

Special Features:

Vde approved; toggle handle color is red - marked with white letters of on/off and i/o; aproximate weight per pole 2.2 ounces; dielectric strength with auxiliary switched terminals 600 volts ac, 60 hertz

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0