

View Online at <https://aerobasegroup.com/nsn/5925-01-487-6017>

**Bushing Length:**

0.380 inches

**Body Length:**

1.562 inches

**Body Width:**

1.281 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

0.875 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.625 inches

**Mounting Surface To Terminal End Distance:**

1.780 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

1 threaded bushing w/panel seal

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

7.5 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

300.0 ac single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

115.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Internal Trip Release Configuration:**

Series trip single location

**Thread Size:**

0.375 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.055 at 200 pct single location and 0.950 at 200 pct single location

**Frequency In Hertz:**

50.0 single location or 60.0 single location

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

4 wire hook

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0