NSN 5925-01-492-0838

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-492-0838

Body Style:

Multipole-single actuator type

Bushing Length:

0.380 inches

Body Length:

1.562 inches

Body Width:

1.281 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

0.875 inches

Center To Center Distance Between Terminals Parallel To Width:

0.625 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.780 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

50.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

500.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 all locations

NSN 5925-01-492-0838

Circuit Breaker - Page 2 of 2

Reset Method:	
Manual	
Main Contact Tripping Mechanism Type:	
Trip free	
Manual Actuator Type And Quantity:	
1 toggle	
Actuator Function:	
Trip-reset	
Actuator Position Designation:	
At pole one	
Internal Trip Release Configuration:	
Series trip all locations	
Thread Size:	
0.375 inches	
Trip Delay Time In Seconds Per Rated Continuous Current:	
0.600 at 200 pct all locations and 6.000 at 200 pct all locations	
Inclosure Protection Type For Which Designed:	
Hermetically sealed and shockproof and vibrationproof	
Special Features:	
50/60 hz. Dc; 400hz long time dellay 135 percent trip	
Unpackaged Unit Weight:	
3.600 ounces	
Thread Series Designator:	
Unef	
Terminal Type And Quantity:	
4 wire hook	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A030a0	

