

View Online at <https://aerobasegroup.com/nsn/5925-01-493-2196>

Body Style:

Multipole-single actuator type

Body Length:

11.000 inches

Body Width:

9.000 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

9.875 inches

Center To Center Distance Between Terminals Parallel To Width:

3.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

9.875 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

3.000 inches

Boss Height:

0.250 inches

Mounting Surface To Terminal End Distance:

8.968 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 threaded stud

Maximum Continuous Load Current Rating Per Pole:

175.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

20000.0 ac all locations

Circuit Protection Type:

Undervoltage all locations

Reset Method:

Manual

Manual Actuator Type And Quantity:

1 toggle

Frequency In Hertz:

60.0 all locations

Precious Material And Location:

Thermal surfaces silver

Test Data Document:

81349-mil-c-17361 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

6 threaded stud

Specification Data:

81349-mil-c-17361 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0