

View Online at <https://aerobasegroup.com/nsn/5925-01-495-5305>

Body Style:

Single pole type

Body Length:

2.490 inches

Body Width:

1.859 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.940 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.060 inches

Fragility Factor:

Moderately rugged

End Application:

5840-01-450-8127

Boss Height:

0.140 inches

Mounting Surface To Terminal End Distance:

2.265 inches

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

2 threaded stud

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

100.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Auxiliary Switch Function And Quantity:

1 control

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 125 pct all locations and 120.000 at 125 pct all locations

Inclosure Protection Type For Which Designed:

Dustproof

Special Features:

One handle per pole, series with auxillary switch, long d

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Thread Series Designator:

Unf

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0