

View Online at <https://aerobasegroup.com/nsn/5925-01-496-6825>

Body Style:

Multipole-single actuator type

Bushing Length:

0.905 inches

Body Length:

1.562 inches

Body Width:

1.280 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

0.875 inches

Center To Center Distance Between Terminals Parallel To Width:

0.625 inches

End Application:

Los angeles class ssn 688, esm/rwb cntro

Mounting Surface To Terminal End Distance:

1.780 inches

Pole Quantity:

2

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

50.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

400.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location and solid state single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 single location

Reset Method:

Manual

Terminal Type And Quantity:

2 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0