

View Online at <https://aerobasegroup.com/nsn/5925-01-496-7496>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

0.130 inches

**Body Length:**

1.260 inches

**Body Width:**

2.000 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.530 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**End Application:**

Panel, Icac

**Mounting Surface To Terminal End Distance:**

2.265 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

1 threaded bushing w/panel seal

**Maximum Continuous Load Current Rating Per Pole:**

10.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

2100.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

115.0 all locations

**Reset Method:**

Manual

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A030a0