NSN 5925-01-498-4755

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-498-4755

Body Style: Multipole-multiple actuator type **Body Length:** 1.562 inches **Body Width:** 1.281 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 0.950 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.625 inches **Switch Contact Arrangement:** Double pole, single throw, normally closed **End Application:** Los angeles class ssn (688), ship control station, enclosure assembly mini station, mode select console **Mounting Surface To Terminal End Distance:** 1.950 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 threaded hole Thready Qty Per Inch (tpi): **Maximum Continuous Load Current Rating Per Pole:** 5.0 amperes ac all locations and 5.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac all locations and 50.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 50.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 800.0 all locations **Reset Method:** Manual

Trip free

Main Contact Tripping Mechanism Type:

NSN 5925-01-498-4755

Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One and two linked
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.138 inches
Switch Location And Position Designation:
External between pole one and two
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant and salt water resistant
Switch Terminal Type:
Tab w/screw
Switch Current Rating And Type In Amps:
5.0 ac
Switch Voltage Rating And Type In Volts:
240.0 ac
Product Name:
Circuit breaker
Frequency In Hertz:
400.00 all locations
Thread Series Designator:
Unc
Terminal Type And Quantity:
4 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0