

View Online at <https://aerobasegroup.com/nsn/5925-01-498-4770>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

1.562 inches

**Body Width:**

1.281 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

0.950 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.625 inches

**Switch Contact Arrangement:**

Double pole, single throw, normally closed

**End Application:**

Los angeles class ssn (688), ship control station, enclosure assembly mini station, mode select console

**Mounting Surface To Terminal End Distance:**

1.950 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

2 threaded hole

**Thready Qty Per Inch (tpi):**

10

**Maximum Continuous Load Current Rating Per Pole:**

1.0 amperes ac all locations and 1.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations and 50.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

10.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

800.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One and two linked

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Switch Location And Position Designation:

External between pole one and two

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant and salt water resistant

Switch Terminal Type:

Tab w/screw

Switch Current Rating And Type In Amps:

1.0 ac

Switch Voltage Rating And Type In Volts:

240.0 ac

Product Name:

Circuit breaker

Frequency In Hertz:

400.00 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A030a0