

View Online at <https://aerobasegroup.com/nsn/5925-01-500-2704>

**Body Style:**

Single pole type

**Bushing Length:**

0.380 inches

**Body Length:**

1.562 inches

**Body Width:**

0.625 inches

**Center To Center Distance Between Terminals Parallel To Length:**

0.906 inches

**Unthreaded Mounting Hole Diameter:**

0.391 inches

**Switch Contact Arrangement:**

Single pole, single throw, normally closed

**End Application:**

7010-01-391-0168

**Mounting Surface To Terminal End Distance:**

1.810 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

1 threaded bushing w/panel seal

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

15.0 amperes ac single location and 15.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac single location and 50.0 dc single location

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Position Designation:**

At pole one

**Thread Size:**

0.375 inches

**Thread Tolerance Class:**

2a external

**Frequency In Hertz:**

400.0 single location

**Unpackaged Unit Weight:**

50.0 grams

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

2 wire hook or 2 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0

**Mil-std (military Standard):**

Mil-prf-39019 spec.