

View Online at <https://aerobasegroup.com/nsn/5925-01-501-5158>

Body Style:

Single pole type

Body Length:

2.490 inches

Body Width:

0.750 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

1.940 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.060 inches

End Application:

5895-01-467-7213

Mounting Surface To Terminal End Distance:

1.894 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded stud

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Thread Size:

0.190 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

63.000 at 125 pct single location

Trip Release Ambient Temperature Rating:

70.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Thread Series Designator:

Unf

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0