

View Online at <https://aerobasegroup.com/nsn/5925-01-501-6457>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

3.015 inches

**Body Width:**

2.490 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

1.940 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.250 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**End Application:**

5895-01-467-7213

**Boss Height:**

1.042 inches

**Mounting Surface To Terminal End Distance:**

2.529 inches

**Pole Quantity:**

4

**Mounting Facility Type And Quantity:**

6 threaded stud

**Maximum Continuous Load Current Rating Per Pole:**

50.0 amperes ac first location

**Operating Voltage Type And Rating Per Pole In Volts:**

28.0 dc fourth location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Thread Size:**

0.138 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

63.000 at 125 pct third location

**Trip Release Ambient Temperature Rating:**

70.0 degrees celsius all locations

**Special Features:**

1st pole has single pole double throw auxiliary switch

**Frequency In Hertz:**

60.0 all locations

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0