

View Online at <https://aerobasegroup.com/nsn/5925-01-501-6465>

**Body Style:**

Single pole type

**Body Length:**

2.490 inches

**Body Width:**

0.750 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

1.940 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.060 inches

**End Application:**

5895-01-467-7213

**Mounting Surface To Terminal End Distance:**

1.894 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 threaded stud

**Maximum Continuous Load Current Rating Per Pole:**

5.0 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:**

80.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal-magnetic single location

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Thread Size:**

0.190 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

53.000 at 125 pct single location

**Trip Release Ambient Tempurature Rating:**

70.0 degrees celsius single location

**Frequency In Hertz:**

60.0 single location

**Thread Series Designator:**

Unf

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0