

View Online at <https://aerobasegroup.com/nsn/5925-01-501-8596>

Body Style:

Multipole-multiple actuator type

Bushing Length:

0.140 inches

Body Length:

3.015 inches

Body Width:

2.490 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

1.940 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.060 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

End Application:

5895-01-467-7213

Boss Height:

1.042 inches

Mounting Surface To Terminal End Distance:

2.404 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 threaded stud

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

63.000 at 125 pct all locations

Trip Release Ambient Temperature Rating:

70.0 degrees celsius all locations

Special Features:

First pole only has single handle - controls both poles; second pole does not protrude through panel - except mounting screws

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0