NSN 5925-01-503-2662

Circuit Breaker - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5925-01-503-2662

Pole Quantity: 3 Mounting Facility Type And Quantity: 6 unthreaded hole Maximum Continuous Load Current Rating Per Pole: 0.500 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 277.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amp 5000.0 ac all locations Trip Release Characteristic: Time delay all locations Reset Method: Manual Frequency In Hertz: 50.0 all locations or 60.0 all locations	s:
Mounting Facility Type And Quantity: 6 unthreaded hole Maximum Continuous Load Current Rating Per Pole: 0.500 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 277.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amp 5000.0 ac all locations Trip Release Characteristic: Time delay all locations Reset Method: Manual Frequency In Hertz: 50.0 all locations or 60.0 all locations	s:
Maximum Continuous Load Current Rating Per Pole: 0.500 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 277.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amp 5000.0 ac all locations Trip Release Characteristic: Time delay all locations Reset Method: Manual Frequency In Hertz: 50.0 all locations or 60.0 all locations	s:
Maximum Continuous Load Current Rating Per Pole: 0.500 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 277.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amp 5000.0 ac all locations Trip Release Characteristic: Time delay all locations Reset Method: Manual Frequency In Hertz: 50.0 all locations or 60.0 all locations	s:
0.500 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 277.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amp 5000.0 ac all locations Trip Release Characteristic: Time delay all locations Reset Method: Manual Frequency In Hertz: 50.0 all locations or 60.0 all locations	s:
Operating Voltage Type And Rating Per Pole In Volts: 277.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amy 5000.0 ac all locations Trip Release Characteristic: Time delay all locations Reset Method: Manual Frequency In Hertz: 50.0 all locations or 60.0 all locations	s:
277.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amp 5000.0 ac all locations Trip Release Characteristic: Time delay all locations Reset Method: Manual Frequency In Hertz: 50.0 all locations or 60.0 all locations	s:
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amp 5000.0 ac all locations Trip Release Characteristic: Time delay all locations Reset Method: Manual Frequency In Hertz: 50.0 all locations or 60.0 all locations	s:
5000.0 ac all locations Trip Release Characteristic: Time delay all locations Reset Method: Manual Frequency In Hertz: 50.0 all locations or 60.0 all locations	s:
Trip Release Characteristic: Time delay all locations Reset Method: Manual Frequency In Hertz: 50.0 all locations or 60.0 all locations	
Time delay all locations Reset Method: Manual Frequency In Hertz: 50.0 all locations or 60.0 all locations	
Reset Method: Manual Frequency In Hertz: 50.0 all locations or 60.0 all locations	
Manual Frequency In Hertz: 50.0 all locations or 60.0 all locations	
Frequency In Hertz: 50.0 all locations or 60.0 all locations	
50.0 all locations or 60.0 all locations	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A030a0	