

View Online at <https://aerobasegroup.com/nsn/5925-01-503-4543>

**Case Material:**

Metal

**End Application:**

Nsn2320-01-432-4847; weapon system - truck, m-915 series, m-916a (let)

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 terminal

**Maximum Continuous Load Current Rating Per Pole:**

10.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

12.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

400.0 single location

**Ultimate Trip Time Per Pole In Seconds:**

3.500 single location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

3.500 at 400 pct single location

**Special Features:**

Terminals - two 10-32 studs; no bracket; length 1.240 inches, width 0.790 inches, height 0.640 inches; operating temperature - minus 10 degrees f to 150 degrees f

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0