

View Online at <https://aerobasegroup.com/nsn/5925-01-503-7853>

**Body Style:**

Single pole type

**Bushing Length:**

0.500 inches

**Body Length:**

1.380 inches

**Body Width:**

0.560 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

0.840 inches

**End Application:**

Nsn 2320-01-452-5579, truck tractor

**Mounting Surface To Terminal End Distance:**

1.660 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

1 threaded stud

**Thready Qty Per Inch (tpi):**

28

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes ac single location and 20.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac single location and 50.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

1000.0 single location

**Ultimate Trip Time Per Pole In Seconds:**

0.150 single location and 0.780 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push button

**Actuator Function:**

Reset

**Internal Trip Release Configuration:**

Series trip single location

**Thread Size:**

0.438 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.150 at 1000 pct single location and 0.780 at 1000 pct single location

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius single location

**Product Name:**

Circuit breaker, manual re-set, 10 amp

**Frequency In Hertz:**

60.0 single location

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

2 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0