

View Online at <https://aerobasegroup.com/nsn/5925-01-503-7854>

Body Style:

Single pole type

Bushing Length:

0.500 inches

Body Length:

1.380 inches

Body Width:

0.560 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.840 inches

End Application:

Nsn 2320-01-452-5579, truck tractor

Mounting Surface To Terminal End Distance:

1.660 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded stud

Thready Qty Per Inch (tpi):

28

Maximum Continuous Load Current Rating Per Pole:

25.0 amperes ac single location and 25.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location and 50.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

1000.0 single location

Ultimate Trip Time Per Pole In Seconds:

0.150 single location and 0.780 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Reset

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.438 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.150 at 1000 pct single location and 0.780 at 1000 pct single location

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Product Name:

Circuit breaker, manual re-set, 10 amp

Frequency In Hertz:

60.0 single location

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0