NSN 5925-01-506-3109

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-506-3109

Single pole type Bushing Length: 0.344 inches Body Length: 2.187 inches Body Width: 0.750 inches Case Material: Metal Center To Center Distance Between Terminals Parallel To Length: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.802 inches and 1.822 inches Fragility Factor: Moderately rugged Mounting Surface To Terminal End Distance: 1.343 inches Pole Quantity: 1 Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Body Style:
0.344 inches Body Length: 2.187 inches Body Width: 0.750 inches Case Material: Metal Center To Center Distance Between Terminals Parallel To Length: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.802 inches and 1.822 inches Fragility Factor: Moderately rugged Mounting Surface To Terminal End Distance: 1.343 inches Pole Quantity: 1 Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 3500.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	
0.344 inches Body Length: 2.187 inches Body Width: 0.750 inches Case Material: Metal Center To Center Distance Between Terminals Parallel To Length: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.802 inches and 1.822 inches Fragility Factor: Moderately rugged Mounting Surface To Terminal End Distance: 1.343 inches Pole Quantity: 1 Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 3500.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Bushing Length:
2.187 inches Body Width: 0.750 inches Case Material: Metal Center To Center Distance Between Terminals Parallel To Length: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.802 inches and 1.822 inches Fragility Factor: Moderately rugged Mounting Surface To Terminal End Distance: 1.343 inches Pole Quantity: 1 Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	
2.187 inches Body Width: 0.750 inches Case Material: Metal Center To Center Distance Between Terminals Parallel To Length: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.802 inches and 1.822 inches Fragility Factor: Moderately rugged Mounting Surface To Terminal End Distance: 1.343 inches Pole Quantity: 1 Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Body Length:
Case Material: Metal Center To Center Distance Between Terminals Parallel To Length: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.802 inches and 1.822 inches Fragility Factor: Moderately rugged Mounting Surface To Terminal End Distance: 1.343 inches Pole Quantity: 1 Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	
Case Material: Metal Center To Center Distance Between Terminals Parallel To Length: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.802 inches and 1.822 inches Fragility Factor: Moderately rugged Mounting Surface To Terminal End Distance: 1.343 inches Pole Quantity: 1 Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Body Width:
Metal Center To Center Distance Between Terminals Parallel To Length: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.802 inches and 1.822 inches Fragility Factor: Moderately rugged Mounting Surface To Terminal End Distance: 1.343 inches Pole Quantity: 1 Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	0.750 inches
Center To Center Distance Between Terminals Parallel To Length: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.802 inches and 1.822 inches Fragility Factor: Moderately rugged Mounting Surface To Terminal End Distance: 1.343 inches Pole Quantity: 1 Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Case Material:
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.802 inches and 1.822 inches Fragility Factor: Moderately rugged Mounting Surface To Terminal End Distance: 1.343 inches Pole Quantity: 1 Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Metal
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.802 inches and 1.822 inches Fragility Factor: Moderately rugged Mounting Surface To Terminal End Distance: 1.343 inches Pole Quantity: 1 Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Center To Center Distance Between Terminals Parallel To Length:
Between 1.802 inches and 1.822 inches Fragility Factor: Moderately rugged Mounting Surface To Terminal End Distance: 1.343 inches Pole Quantity: 1 Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	0.906 inches
Fragility Factor: Moderately rugged Mounting Surface To Terminal End Distance: 1.343 inches Pole Quantity: 1 Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Moderately rugged Mounting Surface To Terminal End Distance: 1.343 inches Pole Quantity: 1 Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Between 1.802 inches and 1.822 inches
Mounting Surface To Terminal End Distance: 1.343 inches Pole Quantity: 1 Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Fragility Factor:
1.343 inches Pole Quantity: 1 Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Moderately rugged
Pole Quantity: 1 Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Mounting Surface To Terminal End Distance:
Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	1.343 inches
Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Pole Quantity:
2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	1
Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Mounting Facility Type And Quantity:
General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	2 threaded hole
Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Storage Type:
Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	General purpose warehouse
Maximum Continuous Load Current Rating Per Pole: 7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Thready Qty Per Inch (tpi):
7.5 amperes ac single location and 7.5 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	32
Operating Voltage Type And Rating Per Pole In Volts: 115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Maximum Continuous Load Current Rating Per Pole:
115.0 ac single location and 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	7.5 amperes ac single location and 7.5 amperes dc single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Operating Voltage Type And Rating Per Pole In Volts:
3500.0 ac single location and 3500.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	115.0 ac single location and 28.0 dc single location
Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
Overcurrent single location Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	3500.0 ac single location and 3500.0 dc single location
Trip Release Method: Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Circuit Protection Type:
Thermal single location Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Overcurrent single location
Trip Release Characteristic: Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Trip Release Method:
Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Thermal single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location	Trip Release Characteristic:
138.0 single location	Time delay single location
-	Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
Reset Method:	138.0 single location
	Reset Method:
Noot money	Reset Method:

Manual

NSN 5925-01-506-3109 Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 push-pull
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
10.000 at 200 pct single location and 70.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Corrosion resistant and dusttight and explosion proof and sand resistant and shockproof and vibration resistant and moisture resistant
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius single location
Frequency In Hertz:
400.0 single location
Unpackaged Unit Weight:
0.078 pounds
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A030a0