

View Online at <https://aerobasegroup.com/nsn/5925-01-509-5850>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

0.375 inches

**Body Length:**

2.000 inches

**Body Width:**

1.500 inches

**Body Height:**

1.750 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.500 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.500 inches

**Unthreaded Mounting Hole Diameter:**

0.375 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

1 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

15.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

65.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

150.0 all locations

**Ultimate Trip Time Per Pole In Seconds:**

6.000 all locations and 70.000 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Internal Trip Release Configuration:**

Series trip all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

6.000 at 150 pct all locations and 70.000 at 150 pct all locations

**Inclosure Protection Type For Which Designed:**

Fungus resistant and moisture resistant and salt water resistant and shock resistant and vibration resistant and water resistant

**Special Features:**

Vented case

**Frequency In Hertz:**

400.0 all locations

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0