

View Online at <https://aerobasegroup.com/nsn/5925-01-509-7871>

Body Style:

Multipole-multiple actuator type

Body Width:

2.265 inches

Unthreaded Mounting Hole Diameter:

0.156 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.060 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

12.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Solid state all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Manual Actuator Type And Quantity:

3 toggle

Actuator Function:

Reset

Trip Delay Time In Seconds Per Rated Continuous Current:

0.150 at 200 pct all locations and 1.500 at 200 pct all locations

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0