

View Online at <https://aerobasegroup.com/nsn/5925-01-511-2811>

Body Length:

2.330 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

End Application:

Sb-4413/spn-3; w/s - an/spn-42t-3, 42t-4; an/spn-46 (v) 1

Boss Height:

0.140 inches

Pole Quantity:

3

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Manual Actuator Type And Quantity:

3 toggle

Trip Delay Time In Seconds Per Rated Continuous Current:

5.000 at 150 pct all locations and 60.000 at 150 pct all locations

Inclosure Protection Type For Which Designed:

Hermetically sealed

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Switch Current Rating And Type In Amps:

10.0 ac and 30.0 ac and 30.0 ac

Switch Voltage Rating And Type In Volts:

240.0 ac

Frequency In Hertz:

400.0 all locations

Test Data Document:

81349-mil-prf-55629 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

6 threaded stud

Specification Data:

81349-mil-prf-55629/5 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0

Mil-std (military Standard):

Mil-prf-55629 spec.