

View Online at <https://aerobasegroup.com/nsn/5925-01-511-2811>

**Body Length:**

2.330 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**End Application:**

Sb-4413/spn-3; w/s - an/spn-42t-3, 42t-4; an/spn-46 (v) 1

**Boss Height:**

0.140 inches

**Pole Quantity:**

3

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

150.0 all locations

**Manual Actuator Type And Quantity:**

3 toggle

**Trip Delay Time In Seconds Per Rated Continuous Current:**

5.000 at 150 pct all locations and 60.000 at 150 pct all locations

**Inclosure Protection Type For Which Designed:**

Hermetically sealed

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius all locations

**Switch Current Rating And Type In Amps:**

10.0 ac and 30.0 ac and 30.0 ac

**Switch Voltage Rating And Type In Volts:**

240.0 ac

**Frequency In Hertz:**

400.0 all locations

**Test Data Document:**

81349-mil-prf-55629 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

6 threaded stud

**Specification Data:**

81349-mil-prf-55629/5 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0

**Mil-std (military Standard):**

Mil-prf-55629 spec.