NSN 5925-01-516-1453

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-516-1453

| Overall Height: |
|--|
| 11.718 inches |
| Body Length: |
| 12.000 inches |
| Body Width: |
| 8.000 inches |
| Case Material: |
| Metal |
| Center To Center Distance Between Terminals Parallel To Length: |
| 9.875 inches |
| Center To Center Distance Between Terminals Parallel To Width: |
| 3.000 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 9.875 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 3.000 inches |
| End Application: |
| Circuit breaker aqb |
| Boss Height: |
| 0.250 inches |
| Pole Quantity: |
| 3 |
| Mounting Facility Type And Quantity: |
| 2 threaded stud |
| Maximum Continuous Load Current Rating Per Pole: |
| 250.0 amperes ac all locations |
| Operating Voltage Type And Rating Per Pole In Volts: |
| 500.0 ac all locations |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: |
| 100000.0 ac all locations |
| Circuit Protection Type: |
| Undervoltage all locations |
| Trip Release Method: |
| Magnetic-hydraulic all locations |
| Trip Release Characteristic: |
| Instantaneous all locations |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
| 130.0 all locations |
| Reset Method: |
| Electric |
| Main Contact Tripping Mechanism Type: |

Nontrip free

NSN 5925-01-516-1453 Circuit Breaker - Page 2 of 2



| Internal Trip Release Configuration: |
|--|
| Shunt trip all locations |
| Thread Size: |
| 0.375 inches |
| Reset Actuator Voltage Rating And Type In Volts: |
| 250.0 ac |
| Frequency In Hertz: |
| 60.0 all locations |
| Thread Series Designator: |
| Unc |
| Terminal Type And Quantity: |
| 3 threaded stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A030a0 |