## NSN 5925-01-517-7229

Circuit Breaker - Page 1 of 1

Fiig: A030a0

Mil-std (military Standard):

Mil-std-202 spec.



View Online at https://aerobasegroup.com/nsn/5925-01-517-7229 **Body Style:** Single pole type **Body Length:** 2.000 inches **Body Width:** 0.750 inches **Body Height:** 2.075 inches **Boss Height:** 0.240 inches **Pole Quantity: Special Features:** Operates in m40.0-85.0 degrees c; insulation resistance not less than 100 megohms at 500 volts dc; dielectric strength withstands 3750 vac, 60 hz for 60 seconds between all electricity isolated terminals, except auxiliary switch terminal shall withstand 600 vac, 60 hz for reg and rec types; operating as a switch the operating life exceeds 10, 000 operations at a rate of 6 per minute when tested as follows 6000 ops at rated current plus 4000 ops at no load; electrical characteristics 0.050-50 amperes; 80vdc max, 240vac max, 50/60 hz and 0.050-30 amperes; 250vac max, 400 hz; one toggle handle per unit; handle color red Frequency In Hertz: 50.0 single location or 60.0 single location **Supplementary Features:** Pct overload-trip time in seconds 100 pct no trip, 125 pct 0.7-12, 150 pct 0.35-7, 200 pct 0.130-3, 400 pct 0.030-1, 600 pct 0.015-0.3, 800 pct 0.01-0.15, 1000 pct 0.008-0.1 **Test Data Document:** Mil-std-202 standard (includes industry or association standards, individual manufactureer standards, etc.). Shelf Life: N/a **Unit Of Measure: Demilitarization:** No