

View Online at <https://aerobasegroup.com/nsn/5925-01-517-7229>

**Body Style:**

Single pole type

**Body Length:**

2.000 inches

**Body Width:**

0.750 inches

**Body Height:**

2.075 inches

**Boss Height:**

0.240 inches

**Pole Quantity:**

1

**Special Features:**

Operates in m40.0-85.0 degrees c; insulation resistance not less than 100 megohms at 500 volts dc; dielectric strength withstands 3750 vac, 60 hz for 60 seconds between all electricity isolated terminals, except auxiliary switch terminal shall withstand 600 vac, 60 hz for reg and rec types; operating as a switch the operating life exceeds 10, 000 operations at a rate of 6 per minute when tested as follows 6000 ops at rated current plus 4000 ops at no load; electrical characteristics 0.050-50 amperes; 80vdc max, 240vac max, 50/60 hz and 0.050-30 amperes; 250vac max, 400 hz; one toggle handle per unit; handle color red

**Frequency In Hertz:**

50.0 single location or 60.0 single location

**Supplementary Features:**

Pct overload-trip time in seconds 100 pct no trip, 125 pct 0.7-12, 150 pct 0.35-7, 200 pct 0.130-3, 400 pct 0.030-1, 600 pct 0.015-0.3, 800 pct 0.01-0.15, 1000 pct 0.008-0.1

**Test Data Document:**

Mil-std-202 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0

**Mil-std (military Standard):**

Mil-std-202 spec.