

View Online at <https://aerobasegroup.com/nsn/5925-01-519-2068>

Body Style:

Single pole type

Bushing Length:

0.250 inches

Body Length:

1.152 inches

Body Width:

0.750 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.704 inches

End Application:

Boeing b757 aircraft

Mounting Surface To Terminal End Distance:

1.860 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac single location and 15.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

200.0 ac single location and 28.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2800.0 ac single location and 4800.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.4688 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

15.000 at 200 pct single location and 55.000 at 200 pct single location and 2.000 at 400 pct single location and 7.000 at 400 pct single location and 1.000 at 600 pct single location and 3.500 at 600 pct single location

Special Features:

Thread class 2a; barrier extends from bottom of breaker 0.500 inch, length is 1.218 inches, and thickness is 0.031 inch

Frequency In Hertz:

400.0 single location

Unpackaged Unit Weight:

0.150 pounds

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0