

View Online at <https://aerobasegroup.com/nsn/5925-01-519-3248>

**Body Style:**

Single pole type

**Bushing Length:**

12.0 millimeters

**Body Length:**

35.0 millimeters

**Body Width:**

17.3 millimeters

**Center To Center Distance Between Terminals Parallel To Length:**

27.8 millimeters

**Mounting Surface To Terminal End Distance:**

44.5 millimeters

**Pole Quantity:**

1

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

5.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

65.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

50.0 dc single location

**Auxiliary Trip Coil Voltage Type And Rating In Volts:**

3000.0 ac single location

**Trip Release Characteristic:**

Time delay single location

**Manual Actuator Type And Quantity:**

1 push-pull

**Thread Size:**

0.500 inches

**Product Name:**

Circuit breaker fast, push/pull

**Special Features:**

Mounting facility threadneck; color black; mounting size 12 mm high, d shape; c w 2 hex nuts, 1 washer with locating pin; 1 legend plate; actuator black color and without marking; auxiliary contact one change over per pole; internal circuit series trip; no remote trip; no illuminated; auxiliary circuit 2 a, 30 v dc; typical life 10, 000 operations; ambient temperature m40.0 to 70.0 degrees c; interrupting capacity 500 a at 50 v dc; vibration 10 g porm 0.76mm; shock 50 g; corrosion 96 hours at 5 pct salt mist; humidity type 240 hours at 95 pct rh; mass approx 30 g

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

2 knife blade

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

No

**Fiig:**

A030a0