

View Online at <https://aerobasegroup.com/nsn/5925-01-519-3664>

Body Style:

Single pole type

Bushing Length:

12.0 millimeters

Body Length:

35.0 millimeters

Body Width:

17.3 millimeters

Center To Center Distance Between Terminals Parallel To Length:

27.8 millimeters

Mounting Surface To Terminal End Distance:

44.5 millimeters

Pole Quantity:

1

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

0.25 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

65.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

50.0 dc single location

Auxiliary Trip Coil Voltage Type And Rating In Volts:

3000.0 ac single location

Trip Release Characteristic:

Instantaneous single location

Manual Actuator Type And Quantity:

1 push-pull

Thread Size:

0.500 inches

Product Name:

Circuit breaker fast, push/pull

Special Features:

Mounting facility threadneck; color black; mounting size 12 mm high, d shape; c w 2 hex nuts, 1 washer with locating pin; 1 legend plate; actuator black color and without marking; auxiliary contact one change over per pole; internal circuit series trip; no remote trip; no illuminated; auxiliary circuit 2 a, 30 v dc; typical life 10, 000 operations; ambient temperature m40.0 to 70.0 degrees c; interrupting capacity 500 a at 50 v dc; vibration 10 g porm 0.76mm; shock 50 g; corrosion 96 hours at 5 pct sale mist; humidity type 240 hours at 95 pct rh; mass approx 30 g

Thread Series Designator:

Un

Terminal Type And Quantity:

2 knife blade

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A030a0